

HARDOX Extreme 2007-02-28

Minimum length: 2000 mm

Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100,0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

The table shows available dimensions for direct order including the maximum length (m)

- Some restrictions, contact your local sales representative for more information
- Outside the range of dimensions

Width (mm)	1000-	-1351	-1500	-1601	-1701	-1801	-1901	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301	
Thickness (mm)	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0-3.7*																						
3.8-4.7*																						
4.8-5.7*																						
5.8-6.7																						
6.8-7.7																						
8.0-8.7																						
8.8-10																						
10.1-13																						
13.1-25					Maximum length 14,5m																	
25.1-26																						
26.1-27																						
27.1-28																						
28.1-29																						
29.1-30																						
30.1-31																						
31.1-32																						
32.1-33																						
33.1-34																						
34.1-35																						
35.1-36																						
36.1-37																						
37.1-38																						
38.1-39																						
39.1-40																						
40.1-45																						
45.1-50																						
50.1-55																						
55.1-60																						
60.1-65																						
65.1-70																						
70.1-75																						
75.1-80																						
80.1-102																						
102.1-115																						
115.1-130																						
130.1-150																						