

HARDOX® 450 PLATE

2018-01-12

HARDOX® 450 SHEET

The table shows available dimensions in mm for direct order including the maximum length.

The table shows available dimensions in mm for direct order including the maximum length. Cut length with mill edges, black

Some restrictions, contact your local sales representative for more information

Some restrictions, please contact product manager or Tech support, techsupport@ssab.com

Outside the range of dimensions

Outside the range of dimensions

Min. length 1500mm

Min. bundle weight 2 ton

Minimum length: 2000 mm

Minimum quantities:

Min. position weight:

3.0-60.0 2.5 tons

60.1-100.0 3.5 tons

100.1-120.0 4.0 tons

120.1- 5.0 tons

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Hardox®.

For thermally cut edges, contact local sales force

Width Thickness	1000- 1350	1351- 1500	1501- 1600	1601- 1700	1701- 1800	1801- 1900	1901- 2000	2001- 2100	2101- 2200	2201- 2300	2301- 2400	2401- 2500	2501- 2600	2601- 2700	2701- 2800	2801- 2900	2901- 3000	3001- 3100	3101- 3200	3201- 3300	3301- 3350	
3.2 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0																						
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0																						
33.1 - 34.0																						
34.1 - 35.0																						
35.1 - 36.0																						
36.1 - 37.0																						
37.1 - 38.0																						
38.1 - 39.0																						
39.1 - 40.0																						
40.1 - 45.0																						
45.1 - 50.0																						
50.1 - 55.0																						
55.1 - 60.0																						
60.1 - 65.0																						
65.1 - 70.0																						
70.1 - 75.0																						
75.1 - 80.0																						
80.1 - 85.0																						
85.1 - 90.0																						
90.1 - 95.0																						
95.1 - 100.0																						
100.1 - 105.0																						
105.1 - 110.0																						
110.1 - 115.0																						
115.1 - 120.0																						
120.1 - 125.0																						
125.1 - 130.0																						

Maximum length 14630 mm

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width. Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

HARDOX® Cold Rolled SHEET

The table shows available dimensions for direct order including the maximum length (mm)

Preferred length 1000 - 8000 mm

Outside the range of dimension

Width Thickness	800	1001- 1000	1251- 1250	1500	>1500
0.70 - 0.90					
1.00 - 1.39					
1.40 - 1.99					
2.00 - 2.10					
>2.10					