

HARDOX® 500 PLATE

2018-01-12

HARDOX® 500 SHEET

The table shows available dimensions in mm for direct order including the maximum length

- Some restrictions, contact your local sales representative for information
- Outside the range of dimensions

Only 1650 mm width, mill edges - 0/+70 mm. Other dimensions must be approved by product manager Hardox®.
For thermally cut edges, contact local sales force

Minimum length: 2000 mm
Minimum quantities:
Thickness: Min. position weight:
3.0-60.0 2.5 tons
60.1-100.0 3.5 tons
100.1-120.0 4.0 tons
120.1- 5.0 tons

The table shows available dimensions in mm for direct order including maximum length
Cut lengths with mill edges, black

Some restrictions, please contact product manager or Tech support, techsupport@ssab.com

Outside the range of dimensions

Min. length 1500 mm
Min. bundle weight 2 ton

Width	1000-1350-1500-1600-1700-1800-1900-2000-2100-2200-2300-2400-2500-2600-2700-2800-2900-3000-3100-3200-3300-3350	1000-1200-1250-1300-1350-1500-1525-1550-1575-1600-1625-1650	950-1000-1050-1100-1150-1200-1250-1300-1350-1400-1450-1500-1550-1600-1650	Thickness	2.00-2.49	2.50-2.99	3.00-3.09	3.10-3.19	3.20-3.99	4.00-4.49	4.50-4.79	4.80-4.99	5.00-5.99	6.00-6.40	6.41-6.50	6.51-7.00	7.10-8.00	8.10-10.0	10.1-25.0	25.1-26.0	26.1-27.0	
3.0-3.7																						
3.8-4.7																						
4.8-5.7																						
5.8-6.7																						
6.8-7.7																						
7.8-8.7																						
8.8-10.0																						
10.1-24.0																						
24.1-25.0																						
25.1-26.0																						
26.1-27.0																						
27.1-28.0																						
28.1-29.0																						
29.1-30.0																						
30.1-31.0																						
31.1-32.0																						
32.1-33.0																						
33.1-34.0																						
34.1-35.0																						
35.1-36.0																						
36.1-37.0																						
37.1-38.0																						
38.1-39.0																						
39.1-40.0																						
40.1-45.0																						
45.1-50.0																						
50.1-55.0																						
55.1-60.0																						
60.1-65.0																						
65.1-70.0																						
70.1-75.0																						
75.1-80.0																						
80.1-100.0																						
100.1-103.0																						
103.1-115.0																						
115.1-130.0																						
130.1-150.0																						

Min position weight is one coil (17 kg/width-mm) cut into cut length sheets of the same thickness and width.
Delivery weight accuracy +/- 10 %, at least - 2 tons / + 3 tons.

